



LCD Module

Product Specification

64128K FC BW-RGB

128 x 64 DOTS Monochrome Display with RGB Backlight

June 8, 2018

Remark:

Contents in this document are subject to change without notice. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Displaytech Ltd.

Displaytech Ltd.

Tel: (852) 2311 2080 ; Fax: (852) 2722 6998 ; Email: sales@displaytech.com.hk

Address: 31E Billion Plaza 2, No. 10 Cheung Yue Street, Cheung Sha Wan, Kowloon,
Hong Kong.

Website: <http://www.displaytech.com.hk>

Revision Record

| REV | CHANGES | DATE |
|------------------------------|---|-------------|
| A0 (Ref. A00 20170407) | First release | Apr 7, 2017 |
| A1 (Ref. A01 20180529) | Updated backlight pins location tolerance in section 2. Mechanical Drawing. | Jun 8, 2018 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |


Table of Content

| | |
|---|-----------|
| Revision Record | 1 |
| 1. General Specifications..... | 3 |
| 2. Mechanical Drawing..... | 4 |
| 3. Interface I/O Terminal..... | 5 |
| 3.1 Pin Description | 6 |
| 4. Electro-Optical Specifications | 6 |
| 4.1 Absolute Maximum Ratings..... | 6 |
| 4.2 Optical Characteristics..... | 7 |
| 4.3 Electrical Characteristics | 7 |
| 4.4 Timing Characteristics | 8 |
| 5. Programming | 13 |
| 5.1 Instruction Table..... | 13 |
| 5.2 Display Data RAM | 14 |
| Appendix A..... | 15 |
| A.1 Packing Method..... | 15 |
| A.2 Part Number Definition | 16 |
| A.3 Definitions of Optical Characteristic | 16 |
| Appendix B | 19 |
| B.1 Quality Units | 19 |
| B.2 Reliability Test..... | 23 |
| B.3 Caution for Using | 23 |

1. General Specifications

| Item | Standard Value | Unit |
|------------------------------|---------------------------------|------|
| Display Pattern | Graphic | |
| Color | Mono | |
| Resolution | 128 x 64 | DOTS |
| Module Dimension (W x H x T) | 58.2 x 41.7 x 5.7 | mm |
| Viewing Area (W x H) | 50 x 25 | mm |
| Active Area (W x H) | 46.05 x 23.01 | mm |
| DOT Size (W x H) | 0.33 x 0.33 | mm |
| DOT Pitch (W x H) | 0.36 x 0.36 | mm |
| LCD Type | FSTN, Positive | |
| Polarizer Type | Transflective | |
| View Direction | 6 H | |
| LCD Controller & Driver | ST7565R | |
| LCD Driving Method | 1/65 duty, 1/9 bias | |
| Interface Type | 4-line SPI; Parallel 6800, 8080 | |
| Backlight Type | LED | |
| Backlight Color | RGB | |
| DC-DC Converter | Build-in | |
| Operation Temperature | -20 ~ +70 | °C |
| Storage Temperature | -30 ~ +80 | °C |

2. Mechanical Drawing



3. Interface I/O Terminal

Block Diagram:

DISPLAY TYPE: FSTN, Transflective, Positive
VIEWING DIRECTION: 6H
DRIVER IC: ST7565R
LOGIC VOLTAGE: 3.0±0.3V
LCD DRIVE VOLTAGE (V_{lcd}): 9.0V
DRIVING METHOD: 1/65 DUTY, 1/9 BIAS
OPERATING TEMPERATURE: -20° ~ +70° C
STORAGE TEMPERATURE: -30° ~ +80° C
INTERFACE CONNECTOR: PIN
ALL UNMARKED TOLERANCE: ±0.2mm
() REFERENCE DIMENSION
PLEASE KINDLY CONFIRM

Pin Description:

| PIN | Symbol | PIN | Symbol |
|-----|--------|-----|--------|
| 1 | CS1 | 15 | VSS |
| 2 | /RES | 16 | VOUT |
| 3 | A0 | 17 | CAP3P |
| 4 | /WR | 18 | CAP1N |
| 5 | /RD | 19 | CAP1P |
| 6 | D0 | 20 | CAP2P |
| 7 | D1 | 21 | CAP2N |
| 8 | D2 | 22 | V4 |
| 9 | D3 | 23 | V3 |
| 10 | D4 | 24 | V2 |
| 11 | D5 | 25 | V1 |
| 12 | D6 | 26 | V0 |
| 13 | D7 | 27 | C86 |
| 14 | VDD | 28 | P/S |

Revision History:

| Rev | Description |
|-----|------------------------------|
| A01 | Update LED-PCB pin tolerance |
| A00 | Original Edition |

| | |
|-----------------------------|----------------------------|
| DRAWN: 陈维江 2018-04-13 | CHECKED: 王彦涵 2018-04-13 |
| APPROVED: 黄宏生 2018-04-13 | |

| | |
|---------|--------------|
| LCM NO: | Rev: 01 |
| DWG NO: | UNITS: mm |
| | SHEET 2 OF 2 |

3.1 Pin Description

| Pin | Symbol | Function Description |
|-----|--------|----------------------------------|
| 1 | CS1 | Chip select (Active low) |
| 2 | /RES | Reset input (Active low) |
| 3 | A0 | Command/data select |
| 4 | /WR | Write execution control pin |
| 5 | /RD | Read execution control pin |
| 6 | D0 | Bi-directional data |
| 7 | D1 | Bi-directional data |
| 8 | D2 | Bi-directional data |
| 9 | D3 | Bi-directional data |
| 10 | D4 | Bi-directional data |
| 11 | D5 | Bi-directional data |
| 12 | D6 | Bi-directional data |
| 13 | D7 | Bi-directional data |
| 14 | VDD | Power supply |
| 15 | VSS | Power ground |
| 16 | VOUT | DC/DC voltage converter |
| 17 | CAP3P | DC/DC voltage converter |
| 18 | CAP1N | DC/DC voltage converter |
| 19 | CAP1P | DC/DC voltage converter |
| 20 | CAP2P | DC/DC voltage converter |
| 21 | CAP2N | DC/DC voltage converter |
| 22 | V4 | Power supply for LCD |
| 23 | V3 | Power supply for LCD |
| 24 | V2 | Power supply for LCD |
| 25 | V1 | Power supply for LCD |
| 26 | V0 | Power supply for LCD |
| 27 | C86 | MPU interface select |
| 28 | P/S | Parallel mode/serial mode select |

4. Electro-Optical Specifications

4.1 Absolute Maximum Ratings

| No | Item | Symbol | Min | Max | Unit |
|----|-------------------------------------|----------------|------|------|------|
| 1 | Power Supply Voltage | VDD | -0.3 | 3.6 | V |
| 2 | Power Supply Voltage (VDD standard) | V0, VOOUT | -0.3 | 13.5 | V |
| 3 | Power Supply Voltage (VDD standard) | V1, V2, V3, V4 | -0.3 | V0 | V |

Note: Operating Temperature and Storage Temperature can be found in *1. General Specifications*.

4.2 Optical Characteristics

| No | Item | Symbol | Condition | Min | Typ | Max | Unit |
|----|----------------------|--------|---|-----|-----|-----|-------------------|
| 1 | Contrast Ratio | Cr | Ta=23±3°C VLCD = Typ. ⁽²⁾ | - | 4.3 | - | - |
| 2 | Response Time | Tr | Ta=23±3°C | - | 150 | 230 | ms |
| | | Tf | | - | 230 | 315 | ms |
| 3 | Viewing Angle | 3H | Cr = 2 Ta=23±3°C | 22 | 28 | - | Deg |
| | | 9H | | 43 | 42 | - | Deg |
| | | 6H | | 37 | 40 | - | Deg |
| | | 12H | | 38 | 40 | - | Deg |
| 4 | R Brightness | Lv | Ta=23±3°C ILED = Typ. | - | 55 | - | cd/m ² |
| | G Brightness | | | - | 130 | - | cd/m ² |
| | B Brightness | | | - | 22 | - | cd/m ² |
| 5 | Luminance Uniformity | ΔLv | | 75 | - | - | % |

Note:

(1) See Appendix Definition of Optical Characteristics for detail.

(2) VLCD can be found in 4.3 Electrical Characteristics.

4.3 Electrical Characteristics

| No | Item | Symbol | Condition | Min | Typ | Max | Unit |
|----|--|------------------------|------------------------------------|---------|-----|---------|------|
| 1 | Power Supply Voltage | VDD | - | 2.7 | 3.0 | 3.3 | V |
| 2 | Power Supply Voltage (LCD drive voltage) | V0 (V _{LCD}) | Ta=23±3°C | 8.6 | 8.8 | 9.0 | V |
| 3 | Current consumption for LCD | I _{dd} | - | - | 0.5 | 1.5 | mA |
| 4 | Input High-level Voltage | V _{IH} | - | 0.8*VDD | | VDD | V |
| 5 | Input Low-level Voltage | V _{IL} | - | VSS | | 0.7*VDD | V |
| 6 | Output High-level Voltage | V _{OH} | - | 0.8*VDD | | VDD | V |
| 7 | Output Low-level Voltage | V _{OL} | - | VSS | | 0.2*VDD | V |
| 8 | Forward Current of Backlight | I _f | Ta=23±3°C | | 60 | | mA |
| 9 | Forward Voltage of Backlight | V _f | I _f = Typ. Ta=23±3°C | 2.6 | 3.2 | 3.8 | V |
| 10 | Luminous Uniformity of Backlight | ΔLv | | 75 | - | - | % |
| 11 | Emission Wavelength | R | | 620 | | 635 | - |
| | | G | 510 | | 535 | - | |
| | | B | 460 | | 480 | - | |

4.4 Timing Characteristics

System Bus Read/Write Characteristics 1 (For the 8080 Series MPU)




Figure 37

Table 24

(VDD = 3.3V, Ta = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | Units |
|------------------------------|----------|--------|-------------|--------|------|-------|
| | | | | Min. | Max. | |
| Address hold time | A0 | tAH8 | | 0 | — | Ns |
| Address setup time | | tAW8 | | 0 | — | |
| System cycle time | | tCYC8 | | 240 | — | |
| Enable L pulse width (WRITE) | WR | tCCLW | | 80 | — | |
| Enable H pulse width (WRITE) | | tCCHW | | 80 | — | |
| Enable L pulse width (READ) | RD | tCCLR | | 140 | — | |
| Enable H pulse width (READ) | | tCCHR | | 80 | — | |
| WRITE Data setup time | D0 to D7 | tDS8 | | 40 | — | |
| WRITE Address hold time | | tDH8 | | 0 | — | |
| READ access time | | tACC8 | CL = 100 pF | — | 70 | |
| READ Output disable time | | tOH8 | CL = 100 pF | 5 | 50 | |

Table 25

(VDD = 2.7V, Ta = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | Units |
|------------------------------|----------|-------------------|-------------|--------|------|-------|
| | | | | Min. | Max. | |
| Address hold time | A0 | t _{AH8} | | 0 | — | ns |
| Address setup time | | t _{AW8} | | 0 | — | |
| System cycle time | | t _{CYC8} | | 400 | — | |
| Enable L pulse width (WRITE) | WR | t _{CCLW} | | 220 | — | |
| Enable H pulse width (WRITE) | | t _{CCHW} | | 180 | — | |
| Enable L pulse width (READ) | RD | t _{CCLR} | | 220 | — | |
| Enable H pulse width (READ) | | t _{CCHR} | | 180 | — | |
| WRITE Data setup time | D0 to D7 | t _{DS8} | | 40 | — | |
| WRITE Address hold time | | t _{DH8} | | 0 | — | |
| READ access time | | t _{ACC8} | CL = 100 pF | — | 140 | |
| READ Output disable time | | t _{OH8} | CL = 100 pF | 10 | 100 | |

*1 The input signal rise time and fall time (tr, tr) is specified at 15 ns or less. When the system cycle time is extremely fast, (tr + tr) ≤ (tcyc8 - tcclw - tcchwh) for (tr + tr) ≤ (tcyc8 - tcclr - tcchr) are specified.

*2 All timing is specified using 20% and 80% of VDD as the reference.

*3 tcclw and tcclr are specified as the overlap between /CS1 being "L" (CS2 = "H") and /WR and /RD being at the "L" level.

System Bus Read/Write Characteristics 2 (For the 6800 Series MPU)




Figure 38

Table 26

(V_{DD} = 3.3V, T_a = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | Units |
|------------------------------|----------|-------------------|-------------|--------|------|-------|
| | | | | Min. | Max. | |
| Address hold time | A0 | t _{AH6} | | 0 | — | ns |
| Address setup time | | t _{AW6} | | 0 | — | |
| System cycle time | | t _{CYC6} | | 240 | — | |
| Enable L pulse width (WRITE) | WR | t _{EWLW} | | 80 | — | |
| Enable H pulse width (WRITE) | | t _{EWHW} | | 80 | — | |
| Enable L pulse width (READ) | RD | t _{EWLR} | | 80 | — | |
| Enable H pulse width (READ) | | t _{EWHR} | | 140 | — | |
| WRITE Data setup time | D0 to D7 | t _{DS6} | | 40 | — | |
| WRITE Address hold time | | t _{DH6} | | 0 | — | |
| READ access time | | t _{ACC6} | CL = 100 pF | — | 70 | |
| READ Output disable time | | t _{OH6} | CL = 100 pF | 5 | 50 | |

Table 27

(V_{DD} = 2.7V, T_a = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | Units |
|------------------------------|----------|-------------------|-------------|--------|------|-------|
| | | | | Min. | Max. | |
| Address hold time | A0 | t _{AH6} | | 0 | — | ns |
| Address setup time | | t _{AW6} | | 0 | — | |
| System cycle time | | t _{CYC6} | | 400 | — | |
| Enable L pulse width (WRITE) | WR | t _{EWLW} | | 220 | — | |
| Enable H pulse width (WRITE) | | t _{EWHW} | | 180 | — | |
| Enable L pulse width (READ) | RD | t _{EWLR} | | 220 | — | |
| Enable H pulse width (READ) | | t _{EWHR} | | 180 | — | |
| WRITE Data setup time | D0 to D7 | t _{DS6} | | 40 | — | |
| WRITE Address hold time | | t _{DH6} | | 0 | — | |
| READ access time | | t _{ACC6} | CL = 100 pF | — | 140 | |
| READ Output disable time | | t _{OH6} | CL = 100 pF | 10 | 100 | |

*1 The input signal rise time and fall time (t_r, t_f) is specified at 15 ns or less. When the system cycle time is extremely fast, (t_r + t_f) ≤ (t_{CYC6} - t_{EWLW} - t_{EWHW}) for (t_r + t_f) ≤ (t_{CYC6} - t_{EWLR} - t_{EWHR}) are specified.

*2 All timing is specified using 20% and 80% of V_{DD} as the reference.

*3 t_{EWLW} and t_{EWLR} are specified as the overlap between CS1 being "L" (CS2 = "H") and E.

The 4-line SPI Interface




Figure 39

Table 28

(VDD = 3.3V, Ta = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | Units |
|-------------------------|--------|------------|-----------|--------|------|-------|
| | | | | Min. | Max. | |
| 4-line SPI Clock Period | SCL | T_{scyc} | | 50 | — | ns |
| SCL "H" pulse width | | T_{shw} | | 25 | — | |
| SCL "L" pulse width | | T_{slw} | | 25 | — | |
| Address setup time | A0 | T_{sas} | | 20 | — | |
| Address hold time | | T_{sah} | | 10 | — | |
| Data setup time | SI | T_{sds} | | 20 | — | |
| Data hold time | | T_{sdh} | | 10 | — | |
| CS-SCL time | CS | T_{css} | | 20 | — | |
| CS-SCL time | | T_{csh} | | 40 | — | |

Table 29

(VDD = 2.7V, Ta = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | Units |
|-------------------------|--------|------------|-----------|--------|------|-------|
| | | | | Min. | Max. | |
| 4-line SPI Clock Period | SCL | T_{scyc} | | 100 | — | ns |
| SCL "H" pulse width | | T_{shw} | | 50 | — | |
| SCL "L" pulse width | | T_{slw} | | 50 | — | |
| Address setup time | A0 | T_{sas} | | 30 | — | |
| Address hold time | | T_{sah} | | 20 | — | |
| Data setup time | SI | T_{sds} | | 30 | — | |
| Data hold time | | T_{sdh} | | 20 | — | |
| CS-SCL time | CS | T_{css} | | 30 | — | |
| CS-SCL time | | T_{csh} | | 60 | — | |

*1 The input signal rise and fall time (t_r , t_f) are specified at 15 ns or less.

*2 All timing is specified using 20% and 80% of VDD as the standard.

Reset Timing




Figure 41

Table 30

(V_{DD} = 3.3V, Ta = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | | Units |
|-----------------------|--------|--------|-----------|--------|------|------|-------|
| | | | | Min. | Typ. | Max. | |
| Reset time | | tr | | — | — | 1.0 | us |
| Reset “L” pulse width | /RES | trw | | 1.0 | — | — | us |

Table 31

(V_{DD} = 2.7V, Ta = -30 to 85°C)

| Item | Signal | Symbol | Condition | Rating | | | Units |
|-----------------------|--------|--------|-----------|--------|------|------|-------|
| | | | | Min. | Typ. | Max. | |
| Reset time | | tr | | — | — | 2.0 | us |
| Reset “L” pulse width | /RES | trw | | 2.0 | — | — | us |

*1 All timing is specified with 20% and 80% of V_{DD} as the standard.

5. Programming

5.1 Instruction Table

Table 16: Table of ST7565R Commands

(Note) *: ignored data

| Command | Command Code | | | | | | | | | | Function | | | |
|---|--------------|-----|-----|------------|----|-------------------------|--------------|----------------------------------|----------------|----|----------|---|---|--|
| | A0 | /RD | /WR | D7 | D6 | D5 | D4 | D3 | D2 | D1 | | D0 | | |
| (1) Display ON/OFF | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 1 | LCD display ON/OFF 0: OFF, 1: ON | |
| (2) Display start line set | 0 | 1 | 0 | 0 | 1 | Display start address | | | | | 1 | Sets the display RAM display start line address | | |
| (3) Page address set | 0 | 1 | 0 | 1 | 0 | 1 | Page address | | | | | 1 | Sets the display RAM page address | |
| (4) Column address set upper bit | 0 | 1 | 0 | 0 | 0 | 0 | 1 | Most significant column address | | | | | 1 | Sets the most significant 4 bits of the display RAM column address. |
| Column address set lower bit | | | | 0 | 0 | 0 | 0 | Least significant column address | | | | | | Sets the least significant 4 bits of the display RAM column address. |
| (5) Status read | 0 | 0 | 1 | Status | | | | 0 | 0 | 0 | 0 | 0 | Reads the status data | |
| (6) Display data write | 1 | 1 | 0 | Write data | | | | | | | 0 | Writes to the display RAM | | |
| (7) Display data read | 1 | 0 | 1 | Read data | | | | | | | 0 | Reads from the display RAM | | |
| (8) ADC select | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | Sets the display RAM address SEG output correspondence 0: normal, 1: reverse | |
| (9) Display normal/reverse | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 0 | 1 | 1 | 0 | 1 | Sets the LCD display normal/ reverse 0: normal, 1: reverse | |
| (10) Display all points ON/OFF | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 1 | Display all points 0: normal display 1: all points ON | |
| (11) LCD bias set | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | Sets the LCD drive voltage bias ratio 0: 1/9 bias, 1: 1/7 bias (ST7565R) | |
| (12) Read-modify-write | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | Column address increment At write: +1 At read: 0 | |
| (13) End | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | Clear read/modify/write | |
| (14) Reset | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | Internal reset | |
| (15) Common output mode select | 0 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | * | * | * | 1 | Select COM output scan direction 0: normal direction 1: reverse direction | |
| (16) Power control set | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 1 | Operating mode | | | 0 | Select internal power supply operating mode | |
| (17) V ₀ voltage regulator internal resistor ratio set | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | Resistor ratio | | | 0 | Select internal resistor ratio(Rb/Ra) mode | |
| (18) Electronic volume mode set | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | Set the V ₀ output voltage electronic volume register | |
| Electronic volume register set | | | | 0 | 0 | Electronic volume value | | | | | 0 | | | |
| (19) Sleep mode set | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 1 | 1 | 0 | 0 | 1 | 0: Sleep mode, 1: Normal mode | |
| (20) Booster ratio set | 0 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | select booster ratio 00: 2x,3x,4x 01: 5x 11: 6x | |
| | | | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | step-up value | | |
| (21) NOP | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | Command for non-operation | |
| (22) Test | 0 | 1 | 0 | 1 | 1 | 1 | 1 | * | * | * | * | * | Command for IC test. Do not use this command | |

Note: See Datasheet of LCD Driver for detail.

5.2 Display Data RAM





Figure 4

Appendix A

A.1 Packing Method A.1.1 Flowchart



Note: Detail refer to goods label in mass production

A.1.2 Carton Label

Carton label is printed with A4 paper.




Remark:

- 1) PART NO = Displaytech part number
- 2) QTY = Quantity of products inside the box
- 3) P/O NO = Customer PO number
- 4) CARTON = Carton number

A.2 Part Number Definition

64128K F C B W-RGB



A.3 Definitions of Optical Characteristic

A.3.1 Contrast Ratio Test

A) Contrast ratio is calculated by the following formula when the output voltage is obtained from the electro-optical test system.


B) Test Condition: Accord to the LCD's driving method and operating voltage (VLCD).

C) Formula:

$$\text{Contrast Ratio (Positive type)} = \frac{\text{Photometer output voltage when non-select waveform is applying}}{\text{Photometer output voltage when select waveform is applying}}$$

$$\text{Contrast Ratio (Negative type)} = \frac{\text{Photometer output voltage when select waveform is applying}}{\text{Photometer output voltage when non-select waveform is applying}}$$


D) Test system:



A.3.2 Response time


A.3.2.1 Positive type

- A) Rise time is defined as the time required for the transmission to change from 90% to 10%.
- B) Fall time is defined as the time required for the transmission to change from 10% to 90%.
- C) On time is defined as the time required for the transmission to change from 100% to 10%.
- D) Off time is defined as the time required for the transmission to change from 0% to 90%.



A.3.2.2 Negative type

- A) Rise time is defined as the time required for the transmission to change from 10% to 90%.
- B) Fall time is defined as the time required for the transmission to change from 90% to 10%.
- C) On time is defined as the time required for the transmission to change from 0% to 90%.
- D) Off time is defined as the time required for the transmission to change from 100% to 10%.




A.3.3 Luminance Measurement

Luminance is a cd/m^2 (nits) measurement of the display's white color (white screen).

All measurements are performed in a dark ambient.

Display luminance is defined as the average value of five (5) white screen measurements. The location of these 5 measurement points is shown in the drawing below.

$$\text{Display Luminance} = \frac{\text{Surface Luminance of all white screen (1+2+3+4+5)}}{5}$$




- | Screen Luminance Measurement Points (5) | |
|---|---------------------------------|
| ● | A: 5mm |
| ● | B: 5mm |
| ● | H / V: Active Area |
| ● | Measuring Equipment: DMS505 |
| ● | Measurement point diameter: 3mm |

A.3.4 White Uniformity Measurement

White luminance uniformity is a cd/m^2 (nits) measurement of the display's white color across the display screen.

All measurements are performed in a dark ambient.

Display luminance uniformity is defined as the percent (%) of luminance value variation over nine (9) white screen measurements. The location of these 9 measurement points is shown in the drawing below.




- | | |
|---|---------------------------------|
| ● | A: 5mm |
| ● | B: 5mm |
| ● | H / V: Active Area |
| ● | Measuring Equipment: DMS505 |
| ● | Measurement point diameter: 3mm |


$$\text{Luminance Uniformity} = \frac{\text{Min Luminance (9 Pts.1- 9)}}{\text{Max Luminance (9 Pts.1- 9)}} \times 100\%$$

A.3.5 Viewing Angle

A) Viewing angle is definition



B) System Block Diagram



Appendix B


B.1 Quality Units

B.1.1 Purpose & Scope


- a. This standard is applicable for mono STN products which were produced by our company. All mono STN products of our company should be subject to this standard;
- b. If some defect item was not defined exactly in this standard, there must be a negotiation between customer and our company;
- c. If customer had special requirements, there also must be a negotiation between customer and our company.

B.1.2 Inspection Conditions

- a. Inspection direction should be perpendicular to LCD surface;
- b. Inspection should be performed under the condition of 20~40W fluorescent lamp;
- c. The distance between inspector's eyes & product surface should be 30cm~50cm when inspection.



B.1.3 Definition of LCD area



B.4 Sampling Plan

a. Sampling Method








According to GB2828.1-2003 (Equivalent to MIL-STD-105/E) General inspection level II.

b. AQL Definition






Major: AQL=0.65 (Please refer to the definition in “B.1.5 & B.1.6 Inspection Criteria”)

Minor: AQL=1.0 (Please refer to the definition in “B.1.5 & B.1.6 Inspection Criteria”)

B.1.5 Inspection Criteria (Not energized)

| No | Defect Name & Illustration | Criteria | Class | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------|--|--|----------------------|---------------------------|-------------|---|---------------------------|-------------|------|------|------|----|---------|------|---------|------|------|------|------|------|------|------|----------|--------|------------------|------|-------------------|--------|------|------|---|----|-------|
| 1.5.1 | Light Leakage | Not allowed | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.2 | Vacuum Bubble | Not allowed | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.3 | Rainbow | According to limit sample | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.4 | Glass Crack  | Not allowed | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.5 | Protrusion - ITO lead  |  Y≤L/3, allowed quantity:2 | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.6 | Protrusion – Edge  | Allowed if protrusion didn't affect dimension. | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.7 | Chip glass - ITO Lead  | Unit: mm <table border="1"> <thead> <tr> <th>S (cm²)</th> <th>X</th> <th>Y</th> <th>Z</th> <th>Allowed Qty</th> </tr> </thead> <tbody> <tr> <td>50<S</td> <td>≤6.0</td> <td>≤L/3</td> <td>≤T</td> <td>3</td> </tr> <tr> <td>12<S≤50</td> <td>≤5.0</td> <td>≤L/3</td> <td>≤T</td> <td>3</td> </tr> <tr> <td>S≤12</td> <td>≤4.0</td> <td>≤L/3</td> <td>≤T</td> <td>3</td> </tr> <tr> <td>S random</td> <td>Random</td> <td>≤0.5, if L/3>0.5</td> <td>≤T/2</td> <td>NC ⁽¹⁾</td> </tr> </tbody> </table> Remark: S was the outline area (big glass area). | S (cm ²) | X | Y | Z | Allowed Qty | 50<S | ≤6.0 | ≤L/3 | ≤T | 3 | 12<S≤50 | ≤5.0 | ≤L/3 | ≤T | 3 | S≤12 | ≤4.0 | ≤L/3 | ≤T | 3 | S random | Random | ≤0.5, if L/3>0.5 | ≤T/2 | NC ⁽¹⁾ | Minor | | | | | |
| S (cm ²) | X | Y | Z | Allowed Qty | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50<S | ≤6.0 | ≤L/3 | ≤T | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12<S≤50 | ≤5.0 | ≤L/3 | ≤T | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S≤12 | ≤4.0 | ≤L/3 | ≤T | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S random | Random | ≤0.5, if L/3>0.5 | ≤T/2 | NC ⁽¹⁾ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.8 | Chip glass – Edge  | Unit: mm <table border="1"> <thead> <tr> <th>S (cm²)</th> <th>X</th> <th>Y*</th> <th>Z</th> <th>Extend width of seal line</th> <th>Allowed Qty</th> </tr> </thead> <tbody> <tr> <td>50<S</td> <td>≤6.0</td> <td>≤2.0</td> <td>≤T</td> <td>≤1/2</td> <td>NC</td> </tr> <tr> <td>12<S≤50</td> <td>≤5.0</td> <td>≤1.5</td> <td>≤T</td> <td>≤1/2</td> <td>NC</td> </tr> <tr> <td>S≤12</td> <td>≤4.0</td> <td>≤1.0</td> <td>≤T</td> <td>≤1/3</td> <td>NC</td> </tr> <tr> <td>S random</td> <td>Random</td> <td>≤0.5</td> <td>≤T/2</td> <td>-</td> <td>NC</td> </tr> </tbody> </table> | S (cm ²) | X | Y* | Z | Extend width of seal line | Allowed Qty | 50<S | ≤6.0 | ≤2.0 | ≤T | ≤1/2 | NC | 12<S≤50 | ≤5.0 | ≤1.5 | ≤T | ≤1/2 | NC | S≤12 | ≤4.0 | ≤1.0 | ≤T | ≤1/3 | NC | S random | Random | ≤0.5 | ≤T/2 | - | NC | Minor |
| S (cm ²) | X | Y* | Z | Extend width of seal line | Allowed Qty | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50<S | ≤6.0 | ≤2.0 | ≤T | ≤1/2 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12<S≤50 | ≤5.0 | ≤1.5 | ≤T | ≤1/2 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S≤12 | ≤4.0 | ≤1.0 | ≤T | ≤1/3 | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S random | Random | ≤0.5 | ≤T/2 | - | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.9 | Chip glass – Corner  | Unit: mm <table border="1"> <thead> <tr> <th>S (cm²)</th> <th>X</th> <th>Y</th> <th>Z</th> <th>Allowed Qty</th> </tr> </thead> <tbody> <tr> <td>50<S</td> <td>≤6.0</td> <td>≤L</td> <td>≤T</td> <td>2</td> </tr> <tr> <td>12<S≤50</td> <td>≤5.0</td> <td>≤L</td> <td>≤T</td> <td>2</td> </tr> <tr> <td>S≤12</td> <td>≤4.0</td> <td>≤L</td> <td>≤T</td> <td>2</td> </tr> </tbody> </table> Remark: If X reach ITO lead, according to the criteria of “1.5.7”. | S (cm ²) | X | Y | Z | Allowed Qty | 50<S | ≤6.0 | ≤L | ≤T | 2 | 12<S≤50 | ≤5.0 | ≤L | ≤T | 2 | S≤12 | ≤4.0 | ≤L | ≤T | 2 | Minor | | | | | | | | | | |
| S (cm ²) | X | Y | Z | Allowed Qty | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 50<S | ≤6.0 | ≤L | ≤T | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12<S≤50 | ≤5.0 | ≤L | ≤T | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S≤12 | ≤4.0 | ≤L | ≤T | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |





Note (1): NC = Not Count

| No | Defect Name & Illustration | Criteria | Class | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|---|---|-------------------|-------------------|------------------|---------------------------|--------------|------------------|-------|-------------|-------|----|----|--------------------------------|---|---|---|---|---|-------------------------|---------------------------------------|---|---|---|---|---------------|---|---|---|---|---|-------|
| 1.5.10 | <p>Circular type</p>  <p>$\Phi = (a+b) / 2$</p> | <p>Suppose $S^{(2)}$ = The area of A, the criteria in A&B is as below,</p> <table border="1"> <thead> <tr> <th>S (cm²) \ Φ (mm)</th> <th>$S \leq 4$</th> <th>$4 < S \leq 12$</th> <th>$12 < S \leq 50$</th> <th>$50 < S \leq 150$</th> <th>$S > 150$</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.10$</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> </tr> <tr> <td>$0.10 < \Phi \leq 0.20$</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> <td>3</td> </tr> <tr> <td>$0.20 < \Phi \leq 0.30$</td> <td>1</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> </tr> <tr> <td>$\Phi > 0.30$</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </tbody> </table> <p>Remark: Bubble, dirt spot, concavo-convex spot & stab spot should be regarded as circular defect. Maximum defect number in 1cm² is 1. Please refer to footmark for the conversion between S & Diagonal.</p> | S (cm ²) \ Φ (mm) | $S \leq 4$ | $4 < S \leq 12$ | $12 < S \leq 50$ | $50 < S \leq 150$ | $S > 150$ | $\Phi \leq 0.10$ | NC | NC | NC | NC | NC | $0.10 < \Phi \leq 0.20$ | 1 | 2 | 2 | 3 | 3 | $0.20 < \Phi \leq 0.30$ | 1 | 1 | 2 | 2 | 3 | $\Phi > 0.30$ | 0 | 0 | 0 | 0 | 0 | Minor |
| S (cm ²) \ Φ (mm) | $S \leq 4$ | $4 < S \leq 12$ | $12 < S \leq 50$ | $50 < S \leq 150$ | $S > 150$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi \leq 0.10$ | NC | NC | NC | NC | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.10 < \Phi \leq 0.20$ | 1 | 2 | 2 | 3 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.20 < \Phi \leq 0.30$ | 1 | 1 | 2 | 2 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi > 0.30$ | 0 | 0 | 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.11 | <p>Linear type</p>  | <p>Suppose S = The area of A, the criteria in a&b is as below,</p> <table border="1"> <thead> <tr> <th>S (cm²) \ $a \& b \Phi$ (mm)</th> <th>$S \leq 4$</th> <th>$4 < S \leq 12$</th> <th>$12 < S \leq 50$</th> <th>$50 < S \leq 150$</th> <th>$S > 150$</th> </tr> </thead> <tbody> <tr> <td>$a \leq 0.03$</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> </tr> <tr> <td>$0.03 < a \leq 0.05, b \leq 3$</td> <td>2</td> <td>3</td> <td>4</td> <td>5</td> <td>6</td> </tr> <tr> <td>$a > 0.05$</td> <td colspan="5">According to the criteria of <1.5.10></td> </tr> </tbody> </table> <p>Remark: Linear scratch, dirt line should be regarded as linear defect. Maximum defect number in 1cm² is 1.</p> | S (cm ²) \ $a \& b \Phi$ (mm) | $S \leq 4$ | $4 < S \leq 12$ | $12 < S \leq 50$ | $50 < S \leq 150$ | $S > 150$ | $a \leq 0.03$ | NC | NC | NC | NC | NC | $0.03 < a \leq 0.05, b \leq 3$ | 2 | 3 | 4 | 5 | 6 | $a > 0.05$ | According to the criteria of <1.5.10> | | | | | Minor | | | | | | |
| S (cm ²) \ $a \& b \Phi$ (mm) | $S \leq 4$ | $4 < S \leq 12$ | $12 < S \leq 50$ | $50 < S \leq 150$ | $S > 150$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $a \leq 0.03$ | NC | NC | NC | NC | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.03 < a \leq 0.05, b \leq 3$ | 2 | 3 | 4 | 5 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $a > 0.05$ | According to the criteria of <1.5.10> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.12 | <p>Polar bubble / Dent</p>  <p>$\Phi = (a+b) / 2$</p> | <p>Suppose S = The area of A, the criteria in A&B is as below,</p> <table border="1"> <thead> <tr> <th>S (cm²) \ Φ (mm)</th> <th>$S \leq 4$</th> <th>$4 < S \leq 12$</th> <th>$12 < S \leq 50$</th> <th>$50 < S \leq 150$</th> <th>$S > 150$</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.15$</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> </tr> <tr> <td>$0.15 < \Phi \leq 0.25$</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> <td>3</td> </tr> <tr> <td>$0.25 < \Phi \leq 0.35$</td> <td>1</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> </tr> <tr> <td>$\Phi > 0.35$</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </tbody> </table> <p>Remark: Maximum defect number in 1cm² is 1. Ignore the dent if it can't be seen in positive angle.</p> | S (cm ²) \ Φ (mm) | $S \leq 4$ | $4 < S \leq 12$ | $12 < S \leq 50$ | $50 < S \leq 150$ | $S > 150$ | $\Phi \leq 0.15$ | NC | NC | NC | NC | NC | $0.15 < \Phi \leq 0.25$ | 1 | 2 | 2 | 3 | 3 | $0.25 < \Phi \leq 0.35$ | 1 | 1 | 2 | 2 | 3 | $\Phi > 0.35$ | 0 | 0 | 0 | 0 | 0 | Minor |
| S (cm ²) \ Φ (mm) | $S \leq 4$ | $4 < S \leq 12$ | $12 < S \leq 50$ | $50 < S \leq 150$ | $S > 150$ | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi \leq 0.15$ | NC | NC | NC | NC | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.15 < \Phi \leq 0.25$ | 1 | 2 | 2 | 3 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $0.25 < \Phi \leq 0.35$ | 1 | 1 | 2 | 2 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\Phi > 0.35$ | 0 | 0 | 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.13 | Polarizer Stab | According to the criteria of <1.5.10> | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.14 | Polarizer Scratch | According to the criteria of <1.5.11> | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.15 | <p>FPC Pinhole</p>  | <table border="1"> <thead> <tr> <th>a</th> <th>b</th> <th>Allowed Qty</th> </tr> </thead> <tbody> <tr> <td>$\leq W/3$</td> <td>$\leq W$</td> <td>NC</td> </tr> <tr> <td>$> W/3$</td> <td>$> W$</td> <td>Not allowed</td> </tr> </tbody> </table> | a | b | Allowed Qty | $\leq W/3$ | $\leq W$ | NC | $> W/3$ | $> W$ | Not allowed | Minor | | | | | | | | | | | | | | | | | | | | | |
| a | b | Allowed Qty | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\leq W/3$ | $\leq W$ | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $> W/3$ | $> W$ | Not allowed | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.16 | <p>FPC Copper Residue</p>  | <table border="1"> <thead> <tr> <th>a</th> <th>b</th> <th>Allowed Qty</th> </tr> </thead> <tbody> <tr> <td>$\leq W/3$</td> <td>$\leq W$</td> <td>NC</td> </tr> <tr> <td>$> W/3$</td> <td>$> W$</td> <td>Not allowed</td> </tr> </tbody> </table> | a | b | Allowed Qty | $\leq W/3$ | $\leq W$ | NC | $> W/3$ | $> W$ | Not allowed | Minor | | | | | | | | | | | | | | | | | | | | | |
| a | b | Allowed Qty | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\leq W/3$ | $\leq W$ | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $> W/3$ | $> W$ | Not allowed | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.17 | FPC Impress / Crease | <table border="1"> <thead> <tr> <th>Shape</th> <th>Allowed Qty</th> </tr> </thead> <tbody> <tr> <td>Moulage / Impress</td> <td>NC</td> </tr> <tr> <td>Crease with a sharp angle</td> <td>Note allowed</td> </tr> </tbody> </table> | Shape | Allowed Qty | Moulage / Impress | NC | Crease with a sharp angle | Note allowed | Minor | | | | | | | | | | | | | | | | | | | | | | | | |
| Shape | Allowed Qty | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Moulage / Impress | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Crease with a sharp angle | Note allowed | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5.18 | Soldering defect | According to the criteria of IPC-A-610C | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Note (2): Suppose Length:Width = 4:3, The conversion between S & diagonal length is as below table,

| S (cm ²) | Diagonal Length (Inch) |
|----------------------|------------------------|
| 4 | 1.13 |
| 12 | 1.95 |
| 50 | 3.99 |
| 150 | 6.91 |

B.1.6 Inspection Criteria (Energized)

| No | Defect Name & Illustration | Criteria | Class | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------------------------|---|---|-----------------------------------|----------|--------|---------|----------|-------|--------|----|----|----|----|----|------------------|---|---|---|---|---|-------------|--------------------------------------|---|---|---|---|--------|---|---|---|---|---|-------|
| 1.6.1 | Circular type when display (Not change along with voltage) | According to the criteria of <1.5.10> | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.2 | Circular type when display (Change along with voltage)  $\Phi = (a+b) / 2$ | Suppose S= The area of A, the criteria in a&b is as below, <table border="1" data-bbox="542 392 1316 616"> <thead> <tr> <th>S (cm²) \ Φ (mm)</th> <th>S≤4</th> <th>4<S≤12</th> <th>12<S≤50</th> <th>50<S≤150</th> <th>S>150</th> </tr> </thead> <tbody> <tr> <td>Φ≤0.30</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> </tr> <tr> <td>0.30<Φ≤0.50</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> <td>3</td> </tr> <tr> <td>0.50<Φ≤0.80</td> <td>1</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> </tr> <tr> <td>Φ>0.80</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </tbody> </table> Remark: Maximum defect number in 1cm ² is 1. | S (cm ²) \ Φ (mm) | S≤4 | 4<S≤12 | 12<S≤50 | 50<S≤150 | S>150 | Φ≤0.30 | NC | NC | NC | NC | NC | 0.30<Φ≤0.50 | 1 | 2 | 2 | 3 | 3 | 0.50<Φ≤0.80 | 1 | 1 | 2 | 2 | 3 | Φ>0.80 | 0 | 0 | 0 | 0 | 0 | Minor |
| S (cm ²) \ Φ (mm) | S≤4 | 4<S≤12 | 12<S≤50 | 50<S≤150 | S>150 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Φ≤0.30 | NC | NC | NC | NC | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.30<Φ≤0.50 | 1 | 2 | 2 | 3 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.50<Φ≤0.80 | 1 | 1 | 2 | 2 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Φ>0.80 | 0 | 0 | 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.3 | Linear type when display (Not change along with voltage) | According to the criteria of <5.1.11> | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.4 | Linear type when display (Change along with voltage)  | Suppose S= The area of A, the criteria in a&b is as below, <table border="1" data-bbox="542 772 1316 952"> <thead> <tr> <th>S (cm²) \ a&b Φ (mm)</th> <th>S≤4</th> <th>4<S≤12</th> <th>12<S≤50</th> <th>50<S≤150</th> <th>S>150</th> </tr> </thead> <tbody> <tr> <td>a≤0.05</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> </tr> <tr> <td>0.05<a≤0.10, b≤5</td> <td>2</td> <td>3</td> <td>4</td> <td>5</td> <td>6</td> </tr> <tr> <td>a>0.10</td> <td colspan="5">According to the criteria of <1.6.2></td> </tr> </tbody> </table> Remark: Maximum defect number in 1cm ² is 1. | S (cm ²) \ a&b Φ (mm) | S≤4 | 4<S≤12 | 12<S≤50 | 50<S≤150 | S>150 | a≤0.05 | NC | NC | NC | NC | NC | 0.05<a≤0.10, b≤5 | 2 | 3 | 4 | 5 | 6 | a>0.10 | According to the criteria of <1.6.2> | | | | | Minor | | | | | | |
| S (cm ²) \ a&b Φ (mm) | S≤4 | 4<S≤12 | 12<S≤50 | 50<S≤150 | S>150 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| a≤0.05 | NC | NC | NC | NC | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.05<a≤0.10, b≤5 | 2 | 3 | 4 | 5 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| a>0.10 | According to the criteria of <1.6.2> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.5 | Pinhole  $\Phi = (a+b) / 2$ | Suppose S= The area of A, the criteria in a&b is as below, <table border="1" data-bbox="542 1008 1316 1232"> <thead> <tr> <th>S (cm²) \ Φ (mm)</th> <th>S≤4</th> <th>4<S≤12</th> <th>12<S≤50</th> <th>50<S≤150</th> <th>S>150</th> </tr> </thead> <tbody> <tr> <td>Φ≤0.10</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> <td>NC</td> </tr> <tr> <td>0.10<Φ≤0.15</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> <td>3</td> </tr> <tr> <td>0.15<Φ≤0.25</td> <td>1</td> <td>1</td> <td>2</td> <td>2</td> <td>3</td> </tr> <tr> <td>Φ>0.25</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </tbody> </table> Remark: Maximum defect number in 1cm ² is 1. | S (cm ²) \ Φ (mm) | S≤4 | 4<S≤12 | 12<S≤50 | 50<S≤150 | S>150 | Φ≤0.10 | NC | NC | NC | NC | NC | 0.10<Φ≤0.15 | 1 | 2 | 2 | 3 | 3 | 0.15<Φ≤0.25 | 1 | 1 | 2 | 2 | 3 | Φ>0.25 | 0 | 0 | 0 | 0 | 0 | Major |
| S (cm ²) \ Φ (mm) | S≤4 | 4<S≤12 | 12<S≤50 | 50<S≤150 | S>150 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Φ≤0.10 | NC | NC | NC | NC | NC | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.10<Φ≤0.15 | 1 | 2 | 2 | 3 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.15<Φ≤0.25 | 1 | 1 | 2 | 2 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Φ>0.25 | 0 | 0 | 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.6 | Segment Distortion | More than 1/5 size in spec is not allowed. | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.7 | Missing Segment (Row or column)  | Not allowed. | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.8 | Abnormal Display | Not allowed. | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.9 | Display inhomogeneity / CR inhomogeneity | According to the approved sample by both sides | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.10 | Too much current | Not allowed. | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.11 | No display | Not allowed. | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.6.12 | No backlight / flicking | Not allowed. | Major | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

B.2 Reliability Test

B.2.1 Standard Specifications for Reliability

B.2.1.1 Test method

There should be no existing conspicuous failure of functions and appearance in LCD after the following tests.

| No | Item | Description |
|----|----------------------------|---|
| 1 | Low Temperature Operating | The sample should be allowed to stand at $(-20\pm 2)^{\circ}\text{C}$ for 96 Hours under driving condition. |
| 2 | High Temperature Operating | The sample should be allowed to stand at $(70\pm 2)^{\circ}\text{C}$ for 96 Hours under driving condition. |
| 3 | Low Temperature Storage | The sample should be allowed to stand at $(-30\pm 3)^{\circ}\text{C}$ for 96 Hours under no-load condition, and then returning it to normal temperature condition, and allowing it stand for 24 hours |
| 4 | High Temperature Storage | The sample should be allowed to stand at $(80\pm 2)^{\circ}\text{C}$ for 96Hours under no-load condition, and then returning it to normal temperature condition, and allowing it stand for 24 hours |
| 5 | Moisture resistance | The sample should be allowed to stand at $(40\pm 2)^{\circ}\text{C}$, $(95\pm 2)\% \text{RH}$ for 96Hours under no-load condition excluding the polarizer, then taking it out and drying it at normal temperature, and allowing it stand for 24 hours |
| 6 | Thermal Shock Resistance | The sample should be allowed to stand the following 5 cycles of operation: T_{STL}^* for 30 minutes -> normal temperature for 5 minutes -> T_{STH}^* for 30 minutes -> normal temperature for 5 minutes, as one cycle, then taking it out and drying it at normal temperature, and allowing it stand for 24 hours |

Note:

- T_{STL} : Lowest Storage Temperature.
- T_{STH} : Highest Storage Temperature.

B.2.1.2 Testing Conditions and Inspection Criteria:

For the final test, the testing sample must be stored at room temperature for 24 hours, after the tests listed above; Standard specifications for Reliability have been executed in order to ensure stability.

| No | Item | Description |
|----|---------------------|---|
| 1 | Current Consumption | The current consumption should be under double of initial test. |
| 2 | Contrast | The contrast must be larger than half of initial test. |
| 3 | Appearance | Appearance defects should not happen. |

B.2.2 Life Time

Functions, performance, appearance, etc. shall be free from remarkable deterioration within 50,000 hours under ordinary operating and storage conditions room temperature ($25\pm 10^{\circ}\text{C}$), normal humidity ($45\pm 20\% \text{RH}$), and in area not exposed to direct sunlight.

B.3 Caution for Using

1. Recommended storage condition: 50~60%RH, $25\pm 5^{\circ}\text{C}$;
2. Avoid direct sunlight. Avoid operating or storage under the temperature which exceeds the standard for a long time;
3. Avoid driving LCD with DC (Direct Current);
4. LCD was made of glass, please avoid any impact or pressure on surface;
5. If the skin contact with liquid crystal incautiously, wash with water for more than 15 minutes. If you feel uncomfortable, please see the doctor immediately;
6. It is prohibited to clean polarizer by ethanol or acetone. Clean polarizer by pure water is recommended;

7. The products should be used within 6 month. Otherwise, the ITO pad and FPC pad maybe be oxidized and cause poor contact, etc.;
8. ESD: TFT module or COG module is sensitive to ESD, effective action should be taken before you touch the products;
9. Avoid contacting the ITO pad by hand and pressing the surface of the LCD. Please take the both sides when you fetch the LCD.